

56014A




DIGITAL METER CONTROL VALVE

INLET CONNECTOR:
RANGE OF FLOW RATE:
RANGE OF PRESSURE REGULATION:
ACCURACY:
WORKING TEMPERATURE:
PUMP TIP:
POWER SUPPLY:
WEIGHT:



1/2" BSP
1 - 25 L / MIN
3 - 70 BAR
± 0.5%
-10°C - +50°C
FLEXIBLE - WITH A SEMI-AUTOMATIC TIP
1 BATERIA 3V
1.5 kg



NOZZLE TIP



LCD DISPLAY



OIL HOSE 4 M

OIL PUMP



RATIO OF PRESSURES: 5:1
MAX. PERFORMANCE: OD 10 DO 14 L/MIN (in acc. type of oil)
WORKING PRESSURE: 30~40 BAR
AIR INTAKE CONNECTOR: 1/4 "QUICK COUPLING
OIL OUTLET CONNECTORS: 1/2 "MALE QUICK COUPLING
LENGTH SUCTION TUBE: 940 mm
DIAMETER OF SUCTION PIPE: 37 mm
APPLIANCE: ENGINE AND TRANSMISSION OILS
WEIGHT: 8 kg



HEAD PUMP



AIR INTAKE VALVE



OIL SCREEN (FILTER)

BARREL TROLLEY

WHEEL: 2 LARGE FULL, 2 SMALL TORSION
SAFETY: CHAIN OF SAFETY. BARREL
CAPACITY: 200 KG



PUMP HOLDER



LARGE FULL WHEELS



SMALL SWIVEL WHEELS